

Technical Information

No. FO 5041

Edition: 01/04 - subject to change

Substitutes: Edition 03/ 02

Status: valid

Xenon Short Arc Lamp

XBO[®] 4500 W/HS OFR

■ Product description

The OSRAM XBO[®] 4500 W/HS OFR is a DC-operated lamp which is especially suited for applications requiring excellent arc stability and a high luminance. The OSRAM XBO[®] 4500 W/HS OFR is designed for horizontal burning position (H = horizontal, S = short)

■ Technical data

Order reference	XBO [®] 4500 W/HS OFR	
Rated lamp wattage	W	4,500
Rated lamp voltage	V	32
Rated lamp current (=)	A	135
Current control range	A	80 - 150
Ignition voltage	kV _P	36
Min. open circuit voltage for cold / hot ignition	V	85 / 110
Luminous flux	lm	190,000
Luminous intensity	cd	22,000
Average luminance	cd/cm ²	95,000
Luminous area w x h *)	mm	1.9 x 6.0
Electrode gap e (cold)	mm	7,0
Lamp length (overall) l ₁	mm	max. 410
Lamp length l ₂	mm	max. 370
LCL	a	mm 171,0
Bulb diameter	d	mm 70
Average service life	h	1,000
Base	Cathode:	SFa 30-7,9
	Anode:	SFa X 30-9,5

*) w = luminance half width value; h = height of luminance area (corresponds to electrode gap, hot)

■ Lamp operation

Maximum permissible base temperature	230°C
Cooling	forced cooling / fan
Min. air flow velocity around discharge vessel	6 m/s
Magnetic arc stabilization	necessary for horizontal operation
Burning position	s 15 (vertical ± 15° ; anode up) ; p 15 (horizontal ± 15°)

