


Low-voltage halogen lamps without reflectors



Product reference	Product number	ANSI	LIF	V	W		t [h]	lm
Low-voltage halogen lamps without reflectors								
64222	4050300327273			6	10	PG22	300	150
64223	4050300017372		M/43	6	10	G4	300	150
64225	4050300006758	ESA	M/29	6	10	G4	100	200
64250 HLX	4050300012407	ESB	M/30	6	20	G4	100	480
64251 HLX	4050300582290			6	20	PG22	100	500
64265 HLX	4008321107053			6	30	G4	100	765
64275	4050300258690		M/137	6	35	G4	50	780
64258	4050300285153			12	20	G4	2000	350
64258 A	4008321050892			12	20	G4	2000	350
64260	4050300099798		M/185	12	30	PG22	50	800
64261	4050300220529		M/130	12	30	G6.35	50	750
64602	4008321107077		M/134	12	50	G6.35	1100	1000
64609 HLX	4050300246253			12	50	PG22	50	1550
64610 HLX	4050300006697	BRL	A1/220	12	50	G6.35	50	1600
64611 HLX	4008321107091			12	50	G6.35	100	1350
62138 HLX	4050300242958			12	100	G6.35	50	2800
64621 HLX	4050300535531			12	100	PG22	2000	2750
64623 HLX	4050300012018	EVA	M/28	12	100	GY6.35	2000	2800
64625 HLX	4050300006703	FCR	A1/215	12	100	GY6.35	50	3600
Product reference								No.
64222	any	9	44	14	1.3x0.8	30	1	
64223	any	9	38	24	1.5x0.7	40	2	
64225	s 90	9.5	31	19.5	1.7x0.65	40	2	
64250 HLX	any	9	31	19.5	2.3x0.8	40	2	
64251 HLX	any	9	40	14	2.3x0.8	30	1	
64265 HLX	any	9	31	19.5	1.5x1.5	40	2	
64275	any	9	40	26	1.2x1.5	40	3	
64258	s 90	9	max. 30	19.5	3.5x0.8 ¹⁾	40	2	
64258 A	s 90	9	max. 33	19.5	3.5x0.8	40	2	
64260	any	9	40	14	2.6x1.3	30	1	
64261	s 90	11.5	44	30	2.6x1.3	40	2	
64602	s 90	11.5	44	30	3.0x3.0	40	2	
64609 HLX	s 90	11.5	48	18	3.3x1.6	30	1	
64610 HLX	s 90	11.5	44	30	3.3x1.6	40	2	
64611 HLX	s 90	11.5	44	30	3.3x1.6	40	2	
62138 HLX	p 90/15	11.5	37	27	2.4x1.8	40	3	
64621 HLX	s 90	11.5	48	18	4.7x2.7	30	1	
64623 HLX	s 90	11.5	44	30	4.7x2.7	40	2	
64625 HLX	s 90	11.5	44	30	4.2x2.3	40	2	

Some lamp models are available as “XENOPHOT®” versions (HLX® types). With xenon instead of krypton as the filler gas, these lamps produce a luminous flux up to 10 per cent higher than lamps with identical electrical data.